



FILCOTEN® Pro 200



FILCOTEN Pro 200
Galvanized Steel



17020228 & 17020229




17020104



17020105



FILCOTEN® Pro Sump Unit 200



FILCOTEN® Pro V 200 Trench Drain

8"/200mm wide channel body with galvanized rail, pre-sloped and neutral sections

Item No.	Product Name	Slope	Length (in.)	Height at Channel End (in.)	Weight (lb.)
10620200	FILCOTEN Pro V 200 Channel 0 with Galvanized Rail - Neutral	0%	39.37	10.43	97.00
10620201	FILCOTEN Pro V 200 Channel 1 with Galvanized Rail	0.5%	39.37	10.43 - 10.63	98.11
10620202	FILCOTEN Pro V 200 Channel 2 with Galvanized Rail	0.5%	39.37	10.63 - 10.83	100.31
10620203	FILCOTEN Pro V 200 Channel 3 with Galvanized Rail	0.5%	39.37	10.83 - 11.02	102.51
10620204	FILCOTEN Pro V 200 Channel 4 with Galvanized Rail	0.5%	39.37	11.02 - 11.22	104.72
10620205	FILCOTEN Pro V 200 Channel 5 with Galvanized Rail	0.5%	39.37	11.22 - 11.42	106.92
10620261	FILCOTEN Pro V 200 Channel 5-0 with Galvanized Rail - Neutral	0%	39.37	11.42	108.30
10620206	FILCOTEN Pro V 200 Channel 6 with Galvanized Rail	0.5%	39.37	11.42 - 11.61	109.13
10620207	FILCOTEN Pro V 200 Channel 7 with Galvanized Rail	0.5%	39.37	11.61 - 11.81	111.33
10620208	FILCOTEN Pro V 200 Channel 8 with Galvanized Rail	0.5%	39.37	11.81 - 12.01	113.54
10620209	FILCOTEN Pro V 200 Channel 9 with Galvanized Rail	0.5%	39.37	12.01 - 12.20	115.74
10620210	FILCOTEN Pro V 200 Channel 10 with Galvanized Rail	0.5%	39.37	12.20 - 12.40	117.95
10620262	FILCOTEN Pro V 200 Channel 10-0 with Galvanized Rail - Neutral	0%	39.37	12.40	118.83
10620264	FILCOTEN Pro V 200 Channel 20-0 with Galvanized Rail - Neutral	0%	39.37	14.37	138.23

FILCOTEN® Pro 200 Grates with fix-connection self-locking system

Item No.	Product Name	Dimensions L / W / H (in.) / (mm)	Load class per EN1433	Max. Design Load (lb.)	Slot/mesh width	Weight (lb.)	Weight (kg.)	Intake Area (in. ² /ft.)	Intake Area (cm ² /m)	Flow Rate Through Grate* (GPM)
17020228	FILCOTEN 200 Galvanized Steel Perforated Grate Class C - 1m	39.37"/8.74"/0.78" 1000/222/20	Class C	56,200	1/4" hole	29.76	13.5	8.03	170	80.702
17020229	FILCOTEN 200 Galvanized Steel Perforated Grate Class C - 1/2 m	19.69"/8.74"/0.78" 500/222/20	Class C	56,200	1/4" hole	14.77	6.7	8.03	170	80.702
17020104	FILCOTEN 200 Ductile Iron Longitudinal Bar Grate Class D - 1/2 m	19.69"/8.74"/0.78" 500/222/20	Class D	89,920	1.14 x 0.51	7.5	3.6	44.41	940	446.24
17020105	FILCOTEN 200 Ductile Iron Slotted Grate Class E - 1/2 m	19.69"/8.74"/0.78" 500/222/20	Class E	134,800	7.87"x 0.55" (200 x 14mm)	18.96	8.6	45.59	965	458.108

*Calculated using simple orifice equation with 1/2 inch head

FILCOTEN® Pro 200 Accessories

Item No.	Product Name	Material	Weight (lb.)
10620290	FILCOTEN Pro V 200 Sump with Galvanized Rail	High-Performance Fiber-Reinforced Concrete	105.82
22512	FILCOTEN 200 Silt Bucket	Plastic	1.54
32089	FILCOTEN 200 Anti-Vandalism Locking Device	Galvanized Steel	0.22
19020216	FILCOTEN 200 End Cap with 8" Outlet	Galvanized Steel	1.10
19020295	FILCOTEN 200 Step Connector Plate	Galvanized Steel	0.44
19021208	FILCOTEN B let 8" - 12"	Galvanized Steel	2.20
70154	FILCOTEN Catch Basin to 8" Pipe Connector	Plastic	2.40
19020230	FILCOTEN Front / End Cap, No Outlet	Galvanized Steel	1.68

NOTE: Will accept 8" pipe